

TM Potential Sensor

The TM measures the soil water potential or matric potential. The soil matric potential is the pressure it takes to pull water out of the soil and is an indicator of stress to plants and crops, can be used to determine soil water fluxes and available water held in the soil. Water equilibrates with the ceramic tip portion of the sensor where the heat capacitance is measured. The matric potential is then calculated from the thermal storage properties of the soil, based on a sensor specific calibration. Because the TM bases its measurements on the thermal properties of the soil, it does not need to be calibrated by the user, does not need to be filled with water, has excellent accuracy and stability, and a much larger range than any conventional tensiometer.



- ☆ Completely maintenance-free (no filling required).
- ☆ Spontaneous reaction to moisture changes.
- ☆ Full measuring range-no measurement gaps in the summer due to dehydration.
- ☆ No frost damage, no influence of salinity.
- ☆ Also measures soil temperature.

TECHNICAL SPECIFICATIONS

Power requirements	7-15 VDC
Output	SDI-12, 0~2.5V
Measurement range	-1000~0Kpa
Measurement accuracy	±0.1Kpa
Temperature measurement range	-40 °C to +80 °C
Temperature resolution	0.1 °C
Current draw	Active: 50mA (for 5 seconds), quiescent: 1.5mA
Warm up time to reading	Up to 5 seconds
Dimensions	23 mm x 15 mm x 125 mm
Cable length	5m, others as desired

SOIL MATRIC POTENTIAL

The soil matric potential (also called water potential) represents the energy it takes to pull water out of soil where the water

is held within the soil by capillary and absorptive forces. The drier the soil, the more energy that is required to pull the water out. Because the pressure can get very high in drier soils.

The matric potential is important for understanding soil water dynamics, such as measuring when crops can become stressed for water, and for determining infiltration rates.

The TM bases its measurement off of the heat capacitance of the soil.

This heat capacitance technology offers advantages over traditional tensiometers or lysimeters by providing more stable measurements without user calibration.

Can have ranges that capture very dry conditions.

Quick response to changes of soil moisture.

Low inner sensor hydrological hysteresis and variability.

Not sensitive to soil salinity.

Quick equilibration time.

Not damaged by frost.

Maintenance-free (no filling required).

No calibration needed.

Beijing Hengrui Changtai Technology Co., Ltd./Address: Room 1413, Building 2, No. 106 Kexing West Road, Changping District, Beijing, China / Postal Code: 102208 / Tel: +86 10 60728968 / Fax: +86 10 50976396 / Web: www.bjhrct.com/ Mobile(WeChat): +86 15311807298/ Email(Skype) : bjhrct@126.com